

ACRYLIC SHEET

# Altuglas® Polish 2

**POLISH 1**

Pour le polissage de l'ALTUGLAS®  
Polishing agent for ALTUGLAS®  
Poliermittel für ALTUGLAS®

**LISH 2**

age de l'ALTUGLAS®  
ent for ALTUGLAS®  
ür ALTUGLAS®

Liquid Polish for  
Altuglas® Acrylic Sheet

## THE ALTUGLAS® TRADEMARK

Altuglas® is the registered tradename of Altuglas International for its polymethylmethacrylate (PMMA) products of all types: cast and extruded, sheets for the sanitary ware market, granules for injection and extrusion, extruded tubes and rods, adhesives and other auxiliary products.

## GENERAL DESCRIPTION

Altuglas® Polish 2 is a combination of mineral abrasives in a mixture of water and aliphatic hydrocarbons with an aromatics content of less than 5%. Altuglas® Polish 2 is used to eliminate slight surface scratches.

Altuglas® Polish 2 is used as a finishing agent after polishing with Altuglas® Polish 1.

## APPLICATIONS

Altuglas® Polish 2 is designed for components made of Altuglas® sheets: cast and extruded, standard and impact.

It is especially well-suited to the following applications :

- windows
- furniture
- poster advertising panels, display stands
- sanitaryware

## PHYSICAL PROPERTIES

Colour : Cream

Density : 0,957 g/cm<sup>3</sup>

Viscosity : 75 ± 15 MPa·s at 20°C

Dry extract : ≈ 7%

## TOXICOLOGY AND SAFETY

Altuglas® Polish 2 has a flash point > 61°C, which makes it inflammable.

It is recommended , therefore, that the product be stored away from all sources of ignition.

Altuglas® Polish 2 can react dangerously with highly oxidizing agents, such as strong acids and halogens.

Altuglas® Polish 2 is not subject to any regulations concerning the labelling and transportation of hazardous materials.

## PACKAGING

Altuglas® Polish 2 is delivered in non-divisible cases containing 10 metal tins of 1 liter.

## PRECAUTIONS FOR STORAGE

Packages must be kept in an area where the temperature is between 0° and 50°C. Freezing temperatures will damage the product. Kept unopened in its original hermetically-sealed packages at 20°C maximum, Altuglas® Polish 2 is guaranteed to keep for one year.

## USE OF ALTUGLAS® POLISH 2

Altuglas® Polish 2 is chemically inert in relation to Altuglas® and other products in our range.

The container must be well shaken before every use.

Soak a cotton pad and rub the surface to be polished in a circular motion until the Altuglas® Polish 2 is completely absorbed. A chamois cloth can be used to accelerate the operation.

For an optimum quality finish, use Altuglas® Polish 2 after using Altuglas® Polish 1.

Complete the operation by wiping (suede-type soft or cotton pad.)

## WARRANTY

The information given in this literature is based on the findings of our research and experience. It is intended as a general guide to the use of our products and must not be considered as a binding specification.

In no way does the information incurs the liability of Altuglas International, especially in case of infringement of the rights of a third party.